




Scope of supply of structured packing (USA)



| Material | Typ | Inclination ° | Surface m ² /m ³ | Weight kg/m ³ | Void fraction % | Thickness mm | Materials | |
|----------|----------------|---------------|---|-----------------------------|--------------------|-----------------|---|---|
| Metal | RMP N 125X | 60 | 38.1 | 4.68 | 99 | 0,15 | Carbon steel, stainless steel, others on request |  |
| | RMP N 125Y | 45 | 38.1 | 4.68 | 99 | 0,15 | | |
| | RMP N 200X | 60 | 61.0 | 4.99 | 99 | 0,1 | | |
| | RMP N 200Y | 45 | 61.0 | 4.99 | 99 | 0,1 | | |
| | RMP N 250X | 60 | 76.3 | 6.24 | 98,7 | 0,1 | | |
| | RMP N 250Y | 45 | 76.3 | 6.24 | 98,8 | 0,1 | | |
| | RMP N 350X | 60 | 106.8 | 8.74 | 98,3 | 0,1 | | |
| | RMP N 350Y | 45 | 106.8 | 8.74 | 98,3 | 0,1 | | |
| Plastics | Hiflow® PLUS#1 | n.a. | 54.9 | 4.06 | 93 | 1 | PP, PPH, PE, others on request |  |
| | Hiflow® PLUS#2 | n.a. | 30.5 | 2.87 | 95 | 1 | | |
| | Hiflow® PLUS#3 | n.a. | 24.4 | 2.18 | 96 | 1 | | |
| | RPP N 250 | 45 | 76.3 | * | * | 1 | | |
| Ceramics | 125X | 60 | 38.1 | 18.72 | 86 | | stoneware |  |
| | 125Y | 45 | 38.1 | 19.97 | 88 | | | |
| | 250X | 60 | 76.3 | 24.96 | 80 | | | |
| | 250Y | 45 | 76.3 | 26.21 | 80 | | | |
| | 350X | 60 | 106.8 | 28.08 | 78 | | | |
| | 350Y | 45 | 106.8 | 28.1 | 78 | | | |
| | 400Y | 45 | 122,0 | 31.2 | 75 | | | |
| | 450X | 60 | 137.3 | 31.2 | 72 | | | |

*: in preparation
Issue: 03.02.2014